



## Ultra-Light Capacity Tweezer-Style Resistance Soldering System

Model: 10501



### Description

American Beauty offers the most advanced and complete line of resistance soldering systems available anywhere in the world. Here are just a few of the advantages that you will find with resistance soldering systems:

- Smash Operational Bottlenecks - Concentrated heat reduces solder time many times over.
- Improve Solder Joint Quality - Poor solder joints are often the result of insufficient heat throughout the joint, creating weak spots.
- Eliminate Thermal Damage - Traditional soldering methods introduce too much heat into surrounding areas damaging critical components or desoldering of previously soldered joints.
- Reduce Liability - Light-weight handpieces cool within seconds greatly reducing likelihood of repetitive strain injury and virtually eliminating the burn risk for the user.
- Solder in Tight Spots - Versatile systems allow easy access to restricted areas.
- Cut down on Energy Consumption - Instant heat means you're not paying to heat a soldering station all day long.
- Save on Maintenance and Consumables - Electrodes last twice as long as soldering tips and don't require constant rewetting.

Stop trying to perform your difficult soldering operation the same old way with the same old tools. Try an American Beauty Resistance Soldering System today.

## Features and Benefits

**100 Watts of (2.6 VAC) Infinitely Variable Power** permits precision soldering and avoids damage caused by thermal overshoot.

**Light-weight, palm-sized hand piece with comfort grip padding** minimizes operator fatigue.

**Copper-coated, stainless steel electrodes** can be easily bent, allowing the user to customize the handpiece to their specific application.

**Footswitch** permits hands-free activation of power, vastly improving control of your applications and virtually eliminating the sparking that is common with other brands of resistance based systems.

## Technical Specifications

<b>Connection Type</b>	Tapered Pins
<b>Wattage</b>	100 watts
<b>Opening between Electrodes</b>	.25 in / 0.64 cm
<b>Electrode Size/Diameter</b>	.078 in / 0.20 cm
<b>Available in a 220-240 VAC?</b>	Yes. Complete International Quote Form
<b>Product Width</b>	8.25 in / 20.96 cm
<b>Product Height</b>	6.50 in / 16.51 cm
<b>Package Weight</b>	5.30 lbs / 2.40 kg
<b>Country of Origin</b>	US
<b>Harmonization Code:</b>	8515.11.0000
<b>RoHS Compliant</b>	Yes
<b>IEC 60335-1, Edition 5.1, 2013-12</b>	Yes
<b>IEC 60335-2-45, Edition 3.2, 2012-01</b>	Yes
<b>WEEE Compliant</b>	Yes
<b>CE Certified</b>	Yes
<b>Warranty Policy</b>	Details
<b>User Manual</b>	User Manual
<b>Product Lgth</b>	8.25

## Applications

Users of this product have stated that they use it for several jobs which include but are not limited to:

1. Soldering soldering wires and miniature components
2. Soldering microwave cable assemblies
3. Assembly of cable harnesses
4. Soldering Z scale model trains, turnout building, etc
5. Splicing traffic signal loops
6. Building prototype models

## Replacement Parts

The following products can be used as replacements for Model 10501 featured on this page:

Model	Product Name
10519	Standard Footswitch
10541	Light Tweezer Style Handpiece
10542	5/64" Steel Electrodes for Resistance Soldering
105A3	100 Watt Infinitely-Variable Resistance Soldering Power Unit

## Accessories

The following products can be used as Accessories for Model 10501 featured on this page:

Model	Product Name
105PTM	Resistance Soldering Precision Timer Module
105V12	Grounding Vise for Holding Parts Hands-Free

## Similar Products

The following products are related (similar model but different specifications, etc.) to Model 10501 featured on this page:

Model	Product Name
10502	Light Capacity Tweezer-Style Resistance Soldering System

## End-Of-Life Instructions

In an effort to reduce waste and comply with WEEE directive, please do not dispose of product. All American Beauty Tools are serviceable and can be repaired and/or replaced. Please contact

manufacturer to make arrangements.